

Mast	Height Extended	Height Retracted	Number Of Sections	Diameter Of Top Section	Diameter Of Base Section	Vertical Headload	Max. Wind Speed Unguyed	Max. Wind Speed With Top Guys	Basic Weight Of Mast
	(m)	(m)		(mm)	(mm)	(kgs)	(kph)	(kph)	(kgs)
NH 5	5.00	1.41	5	38	89.0	18	180	180	15
NH 7	7.00	1.84	5	38	89.0	15	135	160	19
NH 9	9.00	2.30	5	38	89.0	13	108	147	23
NK 6	5.90	1.64	5	50	102	27	164	164	21
NK 9	9.00	2.30	5	50	102	22	114	137	26
NK 11	10.90	2.37	6	38	102	18	96	125	29
NK 16	16.00	4.00	5	50	102	20	65	112	44
NL 8	7.90	1.77	7	50	127	25	140	140	34
NL 9	8.80	2.44	5	76	127	35	130	130	37
NL 10	10.50	2.50	6	63	127	27	110	120	41
NL 12	12.20	2.43	7	50	127	25	95	110	46
NL 16	15.60	4.15	5	76	127	23	78	102	61
NL 22	21.70	4.15	7	50	127	14	56	92	74
NX 8	7.60	1.91	7	76	152	50	155	155	50
NX 10	10.10	2.51	6	89	152	50	120	120	60
NX 14	13.60	2.64	8	63	152	35	92	95	70
NX 18	18.50	4.32	6	89	152	30	70	83	93
NX 25	25.00	4.44	8	63	152	20	52	80	110
NX 30	29.80	4.57	9	50	152	14	44	75	120
NY 7	6.7†	1.62	7	114	238.00	120	150	*	88
NY 10	9.60†	2.22	6	127	238.00	100	126	*	106
NY 12	12.7†	2.31	8	102	238.00	90	90	*	120
NY 14	14.3†	2.35	9	89	238.00	70	80	*	127
NY 18	17.†	3.96	6	127	238.00	50	83	*	170
NY 21	20.7†	4.00	7	114	238.00	40	67	*	183
BR 25	7.60	1.80	6	89.9	152	68	146	*	50
BR 30	9.10	2.10	6	89.9	152	50	120.0	*	54
BR 42	12.8	2.15†	9	89.0	229	68	101	*	120
BR 48	14.6	2.6†	8	102	229	91	90	*	127
BR 52	15.8	2.6†	9	89.9	229	79	72	*	136
BR 56	17.0	2.9†	8	102	229	91	79	*	149
TPM 8	8	1.47	8	31.75	73.66	10	N/A	120	10.2
TPM 10	10	1.75	8	31.75	73.66	8.5	N/A	100	11.61
TPM 12	12	2.02	8	31.75	73.66	7	N/A	85	12.7
GRP 20	6.09	1.65	4	31.8	50.8	8.00	-	-	3.00
GRP 30	10	2.28	5	31.75	57	6	-	-	6
GRP 40	12.2	2.74	5	31.75	57	6	-	-	7
PFC 7.5	7.5	1.93	5	65.6	85.6	12	N/A	120	6
PFC 9	9	2	6	60.6	85.6	10	N/A	100	7
PFC 12	12	2.1	8	50.6	85.6	9	N/A	85	9

† with non rotating base

\* top guys not recommended